

DATASHEET OF PACKING

DB5030 型芳纶纱线盘根

构成: 芳纶及四氟浸纱线编织构成;

特性: --尺寸稳定, 抗压能力强;

--截面密度高, 用于具有结晶析出的介质使用效果极佳;

--抗磨损和抗撕裂强, 可用于磨损性介质和介质中含有颗粒的场合, 不仅盘根会完好, 还能保护泵轴;

适用: 泵、搅拌器、柔和装置、滑阀、反应釜、阀门河接管等。

行业: 推荐用于制药、化工、食品、制糖、造纸和纸浆等工业, 同时能用于过滤/污水处理厂和其他公用设施;



Aramid staple fiber twisted yarm with PTFE impregnation and lubricant.

Main areas of application: Pumps, agitators, blenders, kneading devices, sliding valves, armatures, valves and pipes.

Characteristics:

- Volume and pressure stabilization;
- High cross section density due to PTFE seals, good for crystalized fluids;
- Good protection against wear and tear, in addition, it protects the shaft;
- Suitable for pharmaceutical, chemical, food, sugar, paper and pulp industries as well as filter/sewage treatment plants and communal facilities.

	阀门 Valves	往复泵 Spinning Pumps	旋转泵 Reciprocating Pumps
压力 P (bar)	200	100	25
速度 V (m/s)		2	20
温度 T (°C)	-50~+200 (蒸汽 260)		
PH 值	2~12		